

**AVR CONTROLLED
50°C AMBIENT TEMPERATURE
CLASS "H" TEMP RISE 110°C
(BASE CONTINUOUS RATING)**

**MARINE
60 Hz
6 Pole**

		3 PHASE (6 WIRE)											
POWER FACTOR		0.8		0.8		0.8		0.8		0.8		0.8	
VOLTS :													
STAR		416	440	460	480	600	660 - 690						
DELTA		240	254	266	277	346	380 - 400						
WINDING NO.		312		312		312		312		07		28	
		kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCM 636G		294	235	313	250	313	250	313	250	N/A	N/A	N/A	N/A
HCM 636H		393	314	415	332	415	332	415	332	N/A	N/A	N/A	N/A
HCM 636J		475	380	500	400	500	400	500	400	N/A	N/A	N/A	N/A
HCM 636K		594	475	625	500	625	500	625	500	N/A	N/A	N/A	N/A
PM 736B	1	710	568	750	600	750	600	750	600	750	600	N/A	N/A
PM 736D	1	920	736	975	780	975	780	975	780	975	780	N/A	N/A
PM 736F	1	1240	992	1240	992	1240	992	1240	992	1200	960	N/A	N/A

1 Refer to factory for Delta ratings.

110 / 50

**CLASS
H
TEMP RISE**