

**AVR CONTROLLED**  
**40°C AMBIENT TEMPERATURE**  
**CLASS "F" TEMP RISE 105°C**  
**(BASE CONTINUOUS RATING)**

**INDUSTRIAL**  
**50 Hz**  
**6 Pole**

3 PHASE ( 6 WIRE )						
POWER FACTOR	0.8		0.8		0.8	
VOLTS :						
STAR	380 - 415		440		660 - 690	
DELTA	220 - 240		250		380 - 400	
WINDING NO.	312		312		26	
	kVA	kW	kVA	kW	kVA	kW
HCI 636G	260	208	260	208	N/A	N/A
HCI 636H	350	280	350	280	N/A	N/A
HCI 636J	420	336	420	336	N/A	N/A
HCI 636K	525	420	525	420	N/A	N/A
PI 736B	1	650	520	650	520	N/A
PI 736D	1	850	680	850	680	N/A
PI 736F	1	1200	960	1200	960	N/A

**105 / 40**

**CLASS**  
**F**  
**TEMP RISE**

**AVR CONTROLLED**  
**40°C AMBIENT TEMPERATURE**  
**CLASS "H" TEMP RISE 125°C**  
**(BASE CONTINUOUS RATING)**

**INDUSTRIAL**  
**50 Hz**  
**6 Pole**

3 PHASE ( 6 WIRE )						
POWER FACTOR	0.8		0.8		0.8	
VOLTS :						
STAR	380 - 415		440		660 - 690	
DELTA	220 - 240		250		380 - 400	
WINDING NO.	312		312		26	
	kVA	kW	kVA	kW	kVA	kW
HCI 636G	280	224	280	224	N/A	N/A
HCI 636H	380	304	380	304	N/A	N/A
HCI 636J	450	360	450	360	N/A	N/A
HCI 636K	570	456	570	456	N/A	N/A
PI 736B	1	700	560	700	560	N/A
PI 736D	1	920	736	920	736	N/A
PI 736F	1	1300	1040	1300	1040	N/A

1 Refer to factory for Delta ratings.

**125 / 40**

**CLASS**  
**H**  
**TEMP RISE**