

**AVR CONTROLLED
40°C AMBIENT TEMPERATURE
CLASS "H" TEMP RISE 150°C
(PEAK STANDBY RATING)**

**INDUSTRIAL
50 Hz
6 Pole**

3 PHASE (6 WIRE)							
POWER FACTOR	0.8		0.8		0.8		
VOLTS :							
STAR	380 - 415		440		660 - 690		
DELTA	220 - 240		250		380 - 400		
WINDING NO.	312		312		26		
	kVA	kW	kVA	kW	kVA	kW	
HCI 636G	291	233	291	233	N/A	N/A	
HCI 636H	395	316	395	316	N/A	N/A	
HCI 636J	468	374	468	374	N/A	N/A	
HCI 636K	593	474	593	474	N/A	N/A	
PI 736B	1	730	584	730	584	N/A	N/A
PI 736D	1	960	768	960	768	N/A	N/A
PI 736F	1	1355	1084	1355	1084	N/A	N/A

150 / 40

SB40
AMBIENT

**AVR CONTROLLED
27°C AMBIENT TEMPERATURE
CLASS "H" TEMP RISE 163°C
(PEAK STANDBY RATING)**

**INDUSTRIAL
50 Hz
6 Pole**

3 PHASE (6 WIRE)							
POWER FACTOR	0.8		0.8		0.8		
VOLTS :							
STAR	380 - 415		440		660 - 690		
DELTA	220 - 240		250		380 - 400		
WINDING NO.	312		312		26		
	kVA	kW	kVA	kW	kVA	kW	
HCI 636G	300	240	300	240	N/A	N/A	
HCI 636H	407	326	407	326	N/A	N/A	
HCI 636J	482	386	482	386	N/A	N/A	
HCI 636K	610	488	610	488	N/A	N/A	
PI 736B	1	750	600	750	600	N/A	N/A
PI 736D	1	985	788	985	788	N/A	N/A
PI 736F	1	1390	1112	1390	1112	N/A	N/A

1 Refer to factory for Delta ratings.

163 / 27

SB27
AMBIENT