

**AVR CONTROLLED
40°C AMBIENT TEMPERATURE
CLASS "F" TEMP RISE 105°C
(BASE CONTINUOUS RATING)**

**INDUSTRIAL
60 Hz
6 Pole**

		3 PHASE (6 WIRE)											
POWER FACTOR		0.8		0.8		0.8		0.8		0.8		0.8	
VOLTS :													
STAR		416	440	460	480	600	660 - 690						
DELTA		240	254	266	277	346	380 - 400						
WINDING NO.		312		312		312		312		07		28	
		kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI 636G		306	245	325	260	325	260	325	260	325	260	N/A	N/A
HCI 636H		413	330	438	350	438	350	438	350	438	350	N/A	N/A
HCI 636J		500	400	525	420	525	420	525	420	525	420	N/A	N/A
HCI 636K		625	500	656	525	656	525	656	525	656	525	N/A	N/A
PI 736B	1	750	600	815	652	815	652	815	652	815	652	N/A	N/A
PI 736D	1	970	776	1065	852	1065	852	1065	852	1065	852	N/A	N/A
PI 736F	1	1375	1100	1500	1200	1500	1200	1500	1200	1500	1200	N/A	N/A

105 / 40

**CLASS
F
TEMP RISE**

**AVR CONTROLLED
40°C AMBIENT TEMPERATURE
CLASS "H" TEMP RISE 125°C
(BASE CONTINUOUS RATING)**

**INDUSTRIAL
60 Hz
6 Pole**

		3 PHASE (6 WIRE)											
POWER FACTOR		0.8		0.8		0.8		0.8		0.8		0.8	
VOLTS :													
STAR		416	440	460	480	600	660 - 690						
DELTA		240	254	266	277	346	380 - 400						
WINDING NO.		312		312		312		312		07		28	
		kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI 636G		331	265	350	280	350	280	350	280	350	280	N/A	N/A
HCI 636H		450	360	475	380	475	380	475	380	475	380	N/A	N/A
HCI 636J		531	425	563	450	563	450	563	450	563	450	N/A	N/A
HCI 636K		675	540	713	570	713	570	713	570	713	570	N/A	N/A
PI 736B	1	815	652	875	700	875	700	875	700	875	700	N/A	N/A
PI 736D	1	1050	840	1150	920	1150	920	1150	920	1150	920	N/A	N/A
PI 736F	1	1500	1200	1625	1300	1625	1300	1625	1300	1625	1300	N/A	N/A

1 Refer to factory for Delta ratings.

125 / 40

**CLASS
H
TEMP RISE**