

**AVR CONTROLLED
50°C AMBIENT TEMPERATURE
CLASS "B" TEMP RISE 70°C
(BASE CONTINUOUS RATING)**

**MARINE
50 Hz
6 Pole**

3 PHASE (6 WIRE)							
POWER FACTOR	0.8		0.8		0.8		
VOLTS :							
STAR	380 - 415		440		660 - 690		
DELTA	220 - 240		250		380 - 400		
WINDING NO.	312		312		26		
	kVA	kW	kVA	kW	kVA	kW	
HCM 636G	220	176	220	176	N/A	N/A	
HCM 636H	290	232	290	232	N/A	N/A	
HCM 636J	350	280	350	280	N/A	N/A	
HCM 636K	440	352	440	352	N/A	N/A	
PM 736B	1	480	384	480	384	N/A	N/A
PM 736D	1	630	504	630	504	N/A	N/A
PM 736F	1	800	640	800	640	N/A	N/A

70 / 50

**CLASS
B
TEMP RISE**

**AVR CONTROLLED
50°C AMBIENT TEMPERATURE
CLASS "F" TEMP RISE 90°C
(BASE CONTINUOUS RATING)**

**MARINE
50 Hz
6 Pole**

3 PHASE (6 WIRE)							
POWER FACTOR	0.8		0.8		0.8		
VOLTS :							
STAR	380 - 415		440		660 - 690		
DELTA	220 - 240		250		380 - 400		
WINDING NO.	312		312		26		
	kVA	kW	kVA	kW	kVA	kW	
HCM 636G	250	200	250	200	N/A	N/A	
HCM 636H	330	264	330	264	N/A	N/A	
HCM 636J	400	320	400	320	N/A	N/A	
HCM 636K	505	404	505	404	N/A	N/A	
PM 736B	1	500	400	500	400	N/A	N/A
PM 736D	1	655	524	655	524	N/A	N/A
PM 736F	1	850	680	850	680	N/A	N/A

1 Refer to factory for Delta ratings.

90 / 50

**CLASS
F
TEMP RISE**