

**AVR CONTROLLED**  
**50°C AMBIENT TEMPERATURE**  
**CLASS "B" TEMP RISE 70°C**  
**(BASE CONTINUOUS RATING)**

**MARINE**  
**60 Hz**  
**6 Pole**

3 PHASE ( 6 WIRE )													
POWER FACTOR	0.8		0.8		0.8		0.8		0.8		0.8		
VOLTS :													
STAR	416	440	460	480	600	660 - 690							
DELTA	240	254	266	277	346	380 - 400							
WINDING NO.	312		312		312		312		07		28		
	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW	
HCM 636G	250	200	270	216	270	216	270	216	270	216	N/A	N/A	
HCM 636H	330	264	350	280	350	280	350	280	350	280	N/A	N/A	
HCM 636J	405	324	430	344	430	344	430	344	430	344	N/A	N/A	
HCM 636K	510	408	535	428	535	428	535	428	535	428	N/A	N/A	
PM 736B	1	600	480	650	520	650	520	650	520	650	520	N/A	N/A
PM 736D	1	800	640	845	676	845	676	845	676	845	676	N/A	N/A
PM 736F	1	985	788	1040	832	1040	832	1040	832	1040	832	N/A	N/A

**70 / 50**

**CLASS**  
**B**  
**TEMP RISE**

**AVR CONTROLLED**  
**50°C AMBIENT TEMPERATURE**  
**CLASS "F" TEMP RISE 90°C**  
**(BASE CONTINUOUS RATING)**

**MARINE**  
**60 Hz**  
**6 Pole**

3 PHASE ( 6 WIRE )													
POWER FACTOR	0.8		0.8		0.8		0.8		0.8		0.8		
VOLTS :													
STAR	416	440	460	480	600	660 - 690							
DELTA	240	254	266	277	346	380 - 400							
WINDING NO.	312		312		312		312		07		28		
	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW	
HCM 636G	294	235	313	250	313	250	313	250	313	250	N/A	N/A	
HCM 636H	388	310	413	330	413	330	413	330	413	330	N/A	N/A	
HCM 636J	475	380	500	400	500	400	500	400	500	400	N/A	N/A	
HCM 636K	594	475	625	500	625	500	625	500	625	500	N/A	N/A	
PM 736B	1	710	568	750	600	750	600	750	600	750	600	N/A	N/A
PM 736D	1	920	736	975	780	975	780	975	780	975	780	N/A	N/A
PM 736F	1	1135	908	1200	960	1200	960	1200	960	1200	960	N/A	N/A

1 Refer to factory for Delta ratings.

**90 / 50**

**CLASS**  
**F**  
**TEMP RISE**